


mt-propeller



Type of Aircraft: P.68()
EASA STC: 10014445
FAA STC: SA03420AT
Aircraft EASA TCDS: EASA.A.385
Aircraft FAA TCDS: A31EU
Prop EASA TCDS: P.013
Prop FAA TCDS: N25NE

Applicable Aircraft
 Vulcanair P.68, P.68B, P.68C, P.68 Observer,
 P.68 Observer 2, P.68R
Engines
 Lycoming IO-360-A1B, IO-360-A1B6



STC Kit Contents

Two 3-Blade Full Feathering Constant Speed Propellers
 Two Full Composite Spinner (AFRP)
 One AFM Supplement
 One AFM Supplement
 One Installation Instruction
 One Instruction For Continued Airworthiness
 One Operation and Installation Manual

MTV-12-B-C-F/CF183-59b or
 MTV-12-B-C-F/CF183-53 (wide chord)
 P-1009
 Doc. No. E-1370 (with CF183-59b blades)
 Doc. No. E-2781 (with wide chord CF183-53 blades)
 Doc. No. E-1371 (EASA), E-1444 (FAA)
 Doc. No. E-1372 (EASA), E-1445 (FAA)
 ATA 61-01-24 (E-124)

Propeller Specifications

Full Propeller Designation

Propeller Hub

MTV-12-B-C-F/CF183-59b or
 MTV-12-B-C-F/CF183 -53 (wide chord)
 MTV-12-B-C-F
 Milled single-piece aluminum hub
 CF183-59b or wide chord CF183-53 blade
 Scimitar, light-weight natural composite
 112 lbs; 114,6 lbs with the wide chord CF183-53 blade.
 72 in. (183 cm)
 72 in. (183 cm)
 According to SB 1 () latest issue

Blade

Blade Design

Installed Propellers & Spinner Total Weight

Maximum Diameter

Minimum Diameter

Time Between Overhaul (TBO)

Options

HiGlo® Full Composite Spinner (AFRP) with chrome finish

Replaces

2-Blade Hartzell HC-C2YK-2C(F)/FC7666A-()

Advantages

- Best vibration damping characteristics for almost vibration free propeller operations!
- Bonded on stainless steel leading edge for best erosion protection of the blades!
- Take-off distance over 50 ft remains unchanged with the CF183-59b blades!
- Take-off distance shortened by 55 m with the wide chord CF183-53 blades!
- Enhanced climb by approx. 3% (SL, ISA conditions, MTOW) increasing by altitude!
- Enhanced cruising speeds by approx. 2 to 3 kts (ISA, FL160, 4550 lbs GW) with the CF183-59b blades
- Plus 5 kts with the wide chord CF183-53 blades!
- Approx. 12 lbs less total weight than the original propellers!
- Unlimited blade life!
- Significant inside and outside noise reductions!
- ICAO Annex 16, Vol I, Part II, Chapter X EASA approved noise levels!
- FOD repairable blades!
- Some models equipped with the CF183-53 blades (wide chord) comply with the strict German noise regulations 2010– „Landeplatz-Lärmschutz-Verordnung“ for unrestricted airport operations in Germany and other European Countries in conjunction with the LIESE exhaust!

MT-Propeller Entwicklung GmbH
 Flugplatzstr. 1
 94348 Atting / Germany

Phone: +49 (0) 9429 9409 0
 Fax: +49 (0) 9429 8432
 sales@mt-propeller.com

MT-Propeller USA, Inc.
 1180 Airport Terminal Drive
 DeLand, Florida 32724

Phone: (386) 736-7762
 Fax: (386) 736-7696
 info@mt-propellerusa.com